1738B 4:3PCAP

Open Frame Touch Monitor

Features

AF Coating applied

Optional:

- **No Touch**
- **Privacy Filter**
- **AG Coating**

+10- point capacitive touch screen
+ Energy-saving LED backlight
+ 1280 X 1024 DPI
+ Zero Bezel, Sealed design
+ Dust-proof and Water-proof Front Panel
+ Support OS: Windows/Android/Linux
+ 3 Years warranty



1738B Open Frame Touch Monitor

TDS1738B Open-Frame Touchscreen Specifications	
Color	Black or Silver
Diagonal	17”LED
Aspect Ratio	4:3
Native Resolution	1280 X 1024 DPI at 60Hz
Contrast Ratio	1000：1
Active Display Area	13.30" X 10.64" / 337.92mm X 270.34mm
Number of Colors	16.7 million
Viewing Angle	Horizontal: 85° /80°; Vertical: 85/80°
Response	5ms
Touch Technology	PCAP(Projected Capacitive)-10 touch
Brightness	LED Panel: 250 nits;PCAP Touch: 235 nits
Touch Interface	USB 2.0
Video Interface	HDMI (V1.3 Type A receptacle for HDMI input) VGA (Analog VGA on Female DB-15 connector)
Input Voltage	AC: 100-240 VAC,50/60 Hz; +12VDC +/- 5%
Dimensions	15.16" x 12.5" X 2.09" / 385mm X 317.6 mm X 53mm
Weight	Unpackaged :11LB/5KG
Drop test	1kg of steel ball 1.2 meters down unbroken
Sealability	Touchscreen sealed to bezel Touchscreen sealed to LCD
Temperature	Operating: 0°C-50°C; Storage: -20°C-60°C
Humidity	Operating: 20%-80%; Storage: 10%-95%
Mounting Options	75mm and 100mm VESA mount; Rear Mount; 2 Hole mounting interface on all four sides
Warranty	3-years standard
MTBF	50,000 hours demonstrated
Agency Approvals	FCC; CE; RoHS;CCC
What’s in the Box	VGA Cable(1.8m); USB Cable(1.8m); Power Cable(1.8m)
DC Power	12V3A (DC:2.1mmx5.5mm)